



# AC1200 Wireless Router

1GE WAN+3GE LAN+AC1200

X2



## Overview

The X2 leads the way in the next generation routers, offering dual-band. wireless with all-new 802.11ac Wi-Fi. Its high performance provide the best. wireless connection in both 2.4GHz 300Mbps and 5GHz. The 5GHz band. works at up to 867Mbps, while the 2.4GHz frequency tops 300Mbps, serving anncredible combined bandwidth of 1167Mbps.

## Characteristics

- \* Works seamlessly with all 802.11a/b/g/n/ac devices.
- \* Simultaneous 2.4GHz 300Mbps and 5GHz 867Mbps connections.
- \* 4\* 6dBi high gain antennas.
- \* Easy wireless security setup at a push of the WPS button.
- \* Complete Gigabit ports ensuring high speed Ethernet connection.
- \* Support IPV6 Protocol.

## Specification

Technical items	Descriptions
Standards	IEEE802.3ab, IEEE802.3u
Interface	10/100/1000Mbps WAN port*1 10/100/1000 Mbps LAN port*3
Antenna	6dBi External antenna*4
Button	WPS*1, Reset button*1, WiFi on/off button*1
Power	DC output: 12V 1A
LED indicator	Power*1, WiFi2.4G*1, WiFi5G*1, WAN*1, LAN*3, WPS*1
Data Rate	5 GHz: Up to 867 Mbps 2.4 GHz: Up to 300 Mbps
Transmit Power	2.4G: 16dbm@MCS7 17dbm@OFDM 54M 19dbm@CCK 11M 5G: 17dbm@MCS9 19dbm@MCS7
Basic Features	SSID Broadcast: Enable/Disable Beamforming, MU-MIMO
Wireless Security	WPA-PSK/WPA2-PSK, WPA/WPA2 Wireless Security: Enable/Disable WPS (WiFi Protected Set-up) quick

	encryption
DHCP Server	DHCP Server DHCP Client List DHCP Reservation
Virtual Server	Port Forwarding,DMZ Host
Internet Connection Type	PPPoE, Dynamic IP, Static IP
Operating mode	Wireless Router Mode
Security	Client Filter (support blacklist) ACL Redirect Remote Management
Firewall	Forbid UDP flood attack Forbid TCP flood attack Forbid flood attack Forbid WAN PING from internet
DDNS	Support DDNS
VPN	PPTP client/L2TP client
Features	PPPoE Username/Password Clone
Other	Guest Network Static Routing NTP System Log Backup & Restore configurations Online firmware upgrade Local firmware upgrade
Temperature	Operating Temperature: -10℃ - 50℃ Storage Temperature: -40℃ -70℃.
Humidity	Operating Humidity: (10-90)% RH non-condensing Storage Humidity: (5-95%) RH non-condensing.
Certification	CE/RoHS
Package Content	AC1200 Smart Dual-Band WiFi Router*1 Power Adapter*1 Quick Installation Guide*1

Shenzhen XGTEC Technology Co.,Ltd.

Web: [www.xgtecpon.com](http://www.xgtecpon.com) E-mail: [sales@xgtecpon.com](mailto:sales@xgtecpon.com)

Address:3F Changhong Science and Technology Building, No. 18,South 12 Rd,High-tech Community, Yuehai Street, Nanshan District, Shenzhen China.